

BT910 Product Specification

Model Number	BT910
Application	6V and 12V battery tests 12V start-stop battery tests 12V and 24V cranking/charging system tests
Supported Battery Types	Flooded, AGM Flat, AGM Spiral, EFB, GEL
Supported Battery Ratings	CCA/SAE, EN, EN2, IEC, JIS, DIN, CA/MCA
Operating Range	25 to 2,000 CCA(SAE)
Voltage Range	1V to 32V
Sensor Array	-
Wireless Connection	-
Wired Connection	USB Type-C

Model Number	BT910
Firmware Update	Yes (via PC Software)
Cloud Data Management	-
PC Software	Yes
Test Counter	Yes (with support to recall and print test results of the last 1000 tests)
Printer	2-inch thermal printer
Display	Coloured TFT-LCD (240x320)
Input Device	3-key keypad (up, down, enter)
Clamp-Cable Set Length	0.8 metres (approx. 2.6 feet)
Detachable Cable	Optional
Internal Battery	AA Alkaline

Model Number	BT910
Support	
Voltage Probe	-
Amp Clamp	-
Dimensions (L x W x H)	249 x 103.3 x 77.7 mm (approx. 9.8 x 4 x 3 inches)
Operating Languages	English, French, Spanish, German, Italian, Portuguese, Polish, Dutch, Turkish, Chinese (Traditional), Chinese (Simplified) (more languages possible)