TURBO

ELECTROMECHANICAL GEAR MOTOR FOR SLIDING GATES UP TO 400 Kg, 24 Vdc AND FROM 500 Kg TO 800 Kg, 230 Vac



MODELS

| CODE | DESCRIPTION | PCS PALLET |
|--------|---|------------|
| SC4224 | For sliding gates up to 400 Kg, 24 Vdc motor, control unit with slowdown and electric limit switch, with built-in radio receiver (1 pc) | 36 |
| SC52 | For sliding gates up to 500 Kg, 230 Vac motor, control unit with slowdown and electric limit switch (1 pc) | 36 |
| SC82 | For sliding gates up to 800 Kg, 230 Vac motor, control unit with slowdown and electric limit switch (1 pc) | 36 |






Sturdy and performing motors

| | | SC4224 | SC52 | SC82 |
|------------------------|------|-----------------|-----------------|-----------------|
| MECHANICAL DATA | | | | |
| speed | cm/s | 24 | 16 | 16 |
| torque | Nm | 18 | 16 | 23 |
| working cycle | % | 50 | 30 | 30 |
| ELECTRICAL DATA | | | | |
| control board | | CT102 24 | CT102 | CT102 |
| power | Vac | 230 | 230 | 230 |
| consumption | Α | 1,2 | 1,3 | 1,9 |
| absorbed power | W | 250 | 300 | 450 |
| capacitor | μF | - | 12,5 | 16 |
| thermoprotection | °C | - | 150 | 150 |
| GENERIC DATA | | | | |
| protection degree | IP | 44 | 44 | 44 |
| dimensions (L - D - H) | mm | 320 - 184 - 260 | 320 - 184 - 260 | 320 - 184 - 260 |
| weight | kg | 11 | 12 | 12,5 |
| working temperature | °C | -20 + 55 | -20 + 55 | -20 + 55 |
| gate maximum weight | Kg | 400 | 500 | 800 |


Models of 1100 kg and upward are recommended for condominium installations







DIMENSIONS •••••



····· ACCESSORIES



CREM-P* M4 nylon rack L=1000 M4 zinc coated rack mm for gates up to 800 kg



CREM-8 ** 30x8 mm L=1000 mm



CREM-12 ** M4 zinc coated rack 30x12 mm L=1000 mm



SEL-M Key selector, metal front, plastic back

PC 1



SEL-EU Key selector with European cylinder, metal front and back

PC 1



TS Warning board

PC 1