


Technical data sheet

# OMEGA N55 Adhesive

Adhesive for wind and waterproof adhesion of acrylate or TPU-coated façades and underroof membranes, either to each other, or to connect with concrete, wood and metal.

## Advantages

- plasticizer-resistant
- resistant to oil, petrol, dilute acids and leach
- 1-component
- adhesion on many substrates e.g. wood, concrete, metal

## Field of application

- adhesion at overlaps and joins for OMEGA UDOs 330 and OMEGA facade membranes

## Recommended products

| | |
|---|---|
|  | OMEGA N55 RFU Bottle for dosing |

## Available dimensions

| Article number | Type | Packing unit | Colour | Content - kg | Carton content |
|---|---|---|---|---|---|
| 30MN5 | | Can | yellowish | 2 kg | 1 pieces |
| 30MN55 | | Can | yellowish | 4.5 kg | 1 pieces |
| 8FL05 | | Dosing bottle | | | 1 pieces |

## Technical data

| | | | |
|---|---|---|---|
| Material composition | Nitrile rubber | Working temperature | 0–40 °C |
| Coverage | 40 g/m | Colour | Yellowish |
| Density - g/cm³ | 0.88 g/cm³ | Duration of skin formation,dry/ wet | 10 min / 4 min |
| Storage | 12 months unopened, room temperature | | |

ISOCELL GmbH & Co KG
Gewerbestraße 9
5202 Neumarkt am Wallersee | Österreich
Tel.: +43 6216 4108
office@isocell.at

ISOCELL France
170 Rue Jean Monnet | ZAC de Prat Pip Sud
29490 Guipavas | France
Tél.: +33 2 98 42 11 00
contact@isocell-france.fr

ISOCELL Sverige AB
Torshamnsgatan 35
164 40 Kista | Sverige
Tel.: +46 10 130 25 00
info@isocell.se

ISOCELL Schweiz AG
Herbergstrasse 29
9524 Zuzwil | Suisse /Schweiz
Tel.: +41 71 940 06 72
office@isocell.ch

ISOCELL Bureel België
Außenborner Weg 1 | Schoppen
4770 Amel | Belgique
Tel.: +32 80 39 90 58
office@isocell.be


ISOCELL
www.isocell.com

Processing Guideline

# OMEGA N55 Adhesive

## Info

Wet bonding: apply OMEGA N55 to one of the grease and dust-free surfaces. The sections can be joined during skin-forming time. Priming: on difficult, porous or highly absorbent surfaces OMEGA N55 can also be used as a primer. For this purpose, apply a thin layer to the substrate – allow to air out for approx. 15 min. – then apply adhesive to the sheeting and apply pressure immediately.



ISOCELL GmbH & Co KG
Gewerbestraße 9
5202 Neumarkt am Wallersee | Österreich
Tel.: +43 6216 4108
office@isocell.at

ISOCELL France
170 Rue Jean Monnet | ZAC de Prat Pip Sud
29490 Guipavas | France
Tél.: +33 2 98 42 11 00
contact@isocell-france.fr

ISOCELL Sverige AB
Torshamnsgatan 35
164 40 Kista | Sverige
Tel.: +46 10 130 25 00
info@isocell.se

ISOCELL Schweiz AG
Herbergstrasse 29
9524 Zuzwil | Suisse /Schweiz
Tel.: +41 71 940 06 72
office@isocell.ch

ISOCELL Bureel België
Außenborner Weg 1 | Schoppen
4770 Amel | Belgique
Tel.: +32 80 39 90 58
office@isocell.be

ISOCELL
www.isocell.com

05_2025_EN