



## Technical data sheet

# OMEGA NDB Nail Sealing Tape ESK



A bitumen tape, adhesive on one side, that is attached along the full length between the diffusive roof underlay and the counter-batten. It prevents ingress of rainwater and guarantees optimum windtightness of the construction. Tested for protection from rain by the Austrian Wood Research Association, (Holzforschung Austria Order no. 203/2003/2 T/HH).

## Advantages

- easy to use
- good adhesion on wood and underlays
- good elastic properties

## Field of application

- a seal for nails and screws below the counter battens

## Available dimensions

| Article number | Type | Roll width | Roll length | Carton   | Box/pallet |
|----------------|------|------------|-------------|----------|------------|
| 30MNDI50       | ESK  | 50 mm      | 10 m        | 20 rolls | 16 Boxes   |
| 30MNDI60       | ESK  | 60 mm      | 10 m        | 16 rolls | 24 Boxes   |
| 30MNDI70       | ESK  | 70 mm      | 10 m        | 16 rolls | 24 Boxes   |
| 30MNDI80       | ESK  | 80 mm      | 10 m        | 12 rolls | 24 Boxes   |

## Technical data

|                        |                            |                     |         |
|------------------------|----------------------------|---------------------|---------|
| Material composition   | self-adhesive bitumen tape | Thickness           | 2 mm    |
| Temperature resistance | -40-100 °C                 | Working temperature | 5-40 °C |
| Storage                | 1 year; cool and dry       |                     |         |

# OMEGA NDB Nail Sealing Tape ESK

Attach OMEGA NDB Nail Sealing Tape ESK to the roof sheeting directly beneath the counter-batten. The sealing tape encloses the nail completely and achieves a 100 % sealed penetration point! See Guidelines for OMEGA Roof Underlay The standards according to ÖNORM B 4119 and/or ZVDH (Central Association of German Roofers) must be observed.

