

Q Fittings Care Spray

The greenteQ fittings care spray is a silicone-free, low-viscosity oil for the lubrication and maintenance of window and door fittings. greenteQ fittings care spray is specially designed for the lubrication and maintenance of mechanical rotating parts, hinges, joints, springs and guides.

Properties:



greenteQ fittings care spray lubricates threads, hinges, rollers, springs, window and door handles, precision mechanics and electrical connections (switches, plugs, couplings and cables). It has a water-repellent effect on metal surfaces, e.g. on electrical contacts and outlets, tools etc. greenteQ fittings care spray dissolves marker stains, grease, tar, rubber and adhesive residues. It protects against rust and corrosion as it leaves behind a protective film. It is suitable for all metals. greenteQ fittings care spray loosens rusted and jammed screw and nut

connections as well as corroded and seized metal threaded connections. It penetrates deeply and has excellent capillary and creep properties. The greenteQ fittings care spray is also suitable for woodworking machines, sliding rails, hinges, drawers, saw blades and moulding cutters. It prohibits the short time gumming and is qualified for difficult access areas.

greenteQ fittings care spray - all-in-one solution:

- corrosion protection
- rust dissolver
- lubricant
- contact spray
- cleaning agent

Product picture:



Technical data:



(determined at 23°C and 50% relative humidity)

Standard

Basis		mineral oil basis
Form		aerosol
Appearance		yellowish, transparent
Odour		like a solvent
Density		0.840 g/cm ³
Temperature resistance		up to +80°C

Edition	Content	VBH Item Number
greenteQ Fittings Care Spray	400 ml / can	180.025 / 2006

PRODUCT DATA SHEET

greenteQ

SPRAYS - Fittings Care Spray

Edition 07/2016 | www.vbh.de

Instructions for use, performance and product data, and all other technical data for greenteQ products are general guidelines only. They describe the performance characteristics and material composition of our products. However, they constitute no guarantee according to § 443 BGB. Due to the various application possibilities it is the user's sole responsibility to satisfy himself that the product is adequate for his intended purpose. Any technical consultation with VBH, whether verbal, written or in the form of test samples is for your information only and is absolutely non-committal.

Q Fittings Care Spray

The greenteQ fittings care spray is a silicone-free, low-viscosity oil for the lubrication and maintenance of window and door fittings. greenteQ fittings care spray is specially designed for the lubrication and maintenance of mechanical rotating parts, hinges, joints, springs and guides.

Preparation:



The parts to be treated only need to be roughly free from dirt, rust, oil and grease. Please use a suitable cleaning agent for this purpose.

Users must perform sufficient tests of their own to determine whether the material is suitable for the application in question.

Processing:



Shake the aerosol can well before use. The greenteQ fittings care spray can either be directly applied onto the workpiece to be treated from the can or

indirectly via a cloth, brush or other suitable aids.

Cleaning:



Excess greenteQ fittings care spray can be simply soaked up with an absorbent cloth or rag. We recommend a cleaning agent based on aliphatic hydrocarbons

(brake cleaner, benzine) for thorough cleaning.

Storage and form of delivery:



At -5°C to +30°C. Protect against moisture and direct sunlight! Store upright. Shelf life 18 months once opened.

Form of delivery: aerosol can
Packaging unit: 12 cans / box

Safety instructions:



Please consult the Safety Data Sheet.

General information:



All previous versions of this data sheet are no longer valid.