

Gun Safes

series: **ASG/WS**

grade: **I**

VALBERG


YOU GOT MORE

aser
ut
FFECT

MULTI
LAYER SYSTEM

LFS 30 P
IMP
certified

GRADE I
IMP
certified



Inner compartment
as an option



ASG/WS5

Model										
ASG/WS3*	1345	310	375	1240	205	244	1215	3	6	108
ASG/WS5	1515	400	385	1400	285	232	1273	5	7	160
ASG/WS6	1650	460	450	1530	340	300	1336	6	7	205
ASG/WS8	1650	570	450	1530	450	300	1336	8	7	235
ASG/Combi	1650	850	450	1530	730	300	1336	5/5	9	325
ASG/WS14	1650	880	450	1530	760	300	1336	14	9	325



Key lock
Kaba 71111




Digital lock
Grade B (PS-610)

The outer depth is given without the handle and the lock.


* Grade 1 only (no certified fire protection)



ASG/WS3




ASG/WS5




ASG/WS6



ASG/WS8



ASG/COMBI



ASG/WS14

- Burglary resistance – EN 1143-1, Grade I.
- Fire resistance – LFS 30P according to EN 15659.
- Thickness of door 95 mm, thickness of walls 55 mm.
- The safe body and door are manufactured with two inter-welded walls that are filled with fire resistant concrete.
- Three way locking bolts.
- Integrated relocker, lock secured from drill attacks.
- Standard delivery with double-bit high security key lock with two keys.
- Anchoring to the floor or to the wall.
- Color: RAL 7035 (light grey), also available in RAL 7024 (grey graphite)..