

MAPECOLOR CPU+

Colouring paste for polyurethane-cement Mapefloor CPU+ products range

DESCRIPTION

Mapecolor CPU+ is a product in a paste form based on selected pigments specific for colouring polyurethane-cement **Mapefloor CPU+** products range.

HOW TO USE

Mapecolor CPU+ must be added during the mixing phase of components A, B and C of the **Mapefloor CPU+** products to be pigmented.

Add **Mapecolor CPU+** immediately after pouring component A into the clean, large bucket. Stir a few seconds until a homogeneous mixture is obtained. Then add component B and mix until completely homogenized. Then slowly add all the content of component C and mix with an electric mixer at low speed for at least three minutes until a homogeneous mixture is obtained. Avoid partial mixing.

Do not apply products from the **Mapefloor CPU+** range listed in the table without adding **Mapecolor CPU+**. For more technical and application details, please read the related product technical data sheets.

CONSUMPTION

Product	Comp. A	Comp. B	Comp. C	Mapecolor CPU+
Mapefloor CPU+/MF	2 packs	2 packs	1 bag	2 packs
Mapefloor CPU+/NZ	1 pack	1 pack	1 bag	1 pack
Mapefloor CPU+/RT	1 pack	1 pack	1 bag	1 pack
Mapefloor CPU+/HD	1 pack	1 pack	1 bag	1 pack
Mapefloor CPU+/UD	1 pack	1 pack	1 bag	1 pack
Mapefloor CPU+/SR	1 pack	1 pack	1 bag	1 pack
Mapefloor CPU+/TC	1 pack	1 pack	1 bag	1 pack
Mapefloor CPU+/Cove	1 pack	1 pack	1 bag	1 pack

COLOURS AVAILABLE

Red, green, ochre, grey, beige, blue, orange.

PACKAGING

0,23 kg pouch.

STORAGE

12 months in original sealed packaging, in dry place at a temperature from +10°C to +30°C. Protect from frost.

SAFETY INSTRUCTIONS FOR PREPARATION AND APPLICATION

Instructions for the safe use of our products can be found on the latest version of the Safety Data Sheet, available from our website www.mapei.com.

PRODUCT FOR PROFESSIONAL USE.

TECHNICAL DATA (typical values)

PRODUCT IDENTITY

Consistency:	paste
Colour:	red, green, ochre, grey, beige, blue, orange.
Density:	approx. 1.30÷1.60 g/cm ³

Mixing ratio with the whole Mapefloor CPU+ products range:	A	B	C	Mapecolor CPU+
Mapefloor CPU+/MF	2x2.0	2x2.16	20	2x0.23
Mapefloor CPU+/RT	2.0	2.16	18.5	0.23
Mapefloor CPU+/HD	2.0	2.16	20.5	0.23
Mapefloor CPU+/NZ	2.0	2.16	17	0.23
Mapefloor CPU+/UD	2.0	2.16	19	0.23
Mapefloor CPU+/SR	2.0	2.16	19	0.23
Mapefloor CPU+/COVE	2.0	2.16	25	0.23
Mapefloor CPU+/TC	2.0	2.16	2.5	0.23

WARNING

Although the technical details and recommendations contained in this product data sheet correspond to the best of our knowledge and experience, all the above information must, in every case, be taken as merely indicative and subject to confirmation after long-term practical application; for this reason, anyone who intends to use the product must ensure beforehand that it is suitable for the envisaged application. In every case, the user alone is fully responsible for any consequences deriving from the use of the product.

Please refer to the current version of the Technical Data Sheet, available from our website www.mapei.com

LEGAL NOTICE

The contents of this Technical Data Sheet ("TDS") may be copied into another project-related document, but the resulting document shall not supplement or replace requirements per the TDS in force at the time of the MAPEI product installation.

The most up-to-date TDS can be downloaded from our website www.mapei.com.

ANY ALTERATION TO THE WORDING OR REQUIREMENTS CONTAINED OR DERIVED FROM THIS TDS
EXCLUDES THE RESPONSIBILITY OF MAPEI.

All relevant references for the product are available upon request and from www.mapei.com

Mapei S.p.A.

Via Cafiero, 22, 20158, Milano



+39-02-376731



www.mapei.com



mapei@mapei.it

8994-1-2023 en (IT)

Any reproduction of texts, photos and illustrations published here is prohibited and subject to
prosecution

