

HOPE 14.3L -R1

- Flexible capacity from 14.3kWh to 686.4kWh
- Compact size and easy installation
- High energy density and efficiency
- Excellent safety of LiFePO4 battery
- Long lifespan, 10 years warranty



P O W E R
- I N G O
T O M O R -
R R O W O

Datasheet	HOPE 14.3L-R1
System data	
Battery type	LiFePO4
Nominal voltage	51.2V
Normal capacity	14.3kWh
Usable capacity	13.3kWh
Operating voltage	40~58.4V
Max. Charge/Discharge current	220A
Peak charging/ discharging current	700A/200 us
DOD	90%
General	
Dimension (W/H/D)	478/812/265mm
Weight	<120kg
Installation	Wall-mounted or floor-standing
Altitude	<2000 m
IP Protection	IP20
Operating temperature	Chg: 0~55°C/Dsg: -20 ~ 55°C
Storage temperature*	-20 ~ 45°C
Features	
Cycle life	8000 (0.5C , 80% DOD, @25 °C)
Cooling	Natural convection
System connection	Max. 48 pcs in paralle
Communication port	CAN/RS485
Warranty: 5 years / 10 years	Yes /Optional
CE(EMC), UN38.3, MSDS, ROHS, IEC62619	

* Suggested storage temperature is -10~40 °C